

Plug & Play Network Camera

VSN-90BL/4 Plug & Play IP IR Bullet Camera

Features

- Easily access the video from anywhere in the world via the ID/password (Through accompanied video management software, no complicated DNS settings needed)
- 3GPP/ISMA support
- Dual video streaming with separate frame rate/resolution/bandwidth settings for PC and mobile.
- Connect up to 20 users simultaneously
- Supports enhanced MPEG-4 compression
- Supports resolution of up to full D1 at 30 fps.
- Motion Detection recording and E-mail/FTP snapshot notification
- Event scheduling.
- 1/3" Sony CCD
- 28 IR LEDs ; IR Distance 20 Meter
- Weatherproof housing & bracket included



Specifications

Item	Weatherproof Network IR Bullet Camera
Network Interface	Ethernet 10BaseT/100BaseTX, Auto-MDIX, RJ-45
Video Compression	MPEG-4 Part 2 (ISO/IEC 14496-2) With Motion Detection, Profiles: Sample Profile, Level 0-3
Video Streaming	MPEG-4 (Controllable Frame Rate and Bandwidth)
Resolution	176x120, 352x240, 720x480
Frame Rate	Up to 30 fps in All Resolutions
Image Setting	Resolution
	Bandwidth
	Frame Rate
Security	Web Management Username, Password Protection Video Display ID/ Password Protection
Supported protocols	IPv4, HTTP, TCP, ICMP, RTSP RTP, UDP, IGMP, RTCP, SMTP, FTP, DHCP, UPnP, ARP, DNS, and PPPoE
Video Management	Web-Based Configuration
SpecoView Software	Surveillance Application for Viewing and Archiving Up to 16 IP Camera
Hardware Requirements	Pentium 4 CPU 1.0 GHz or higher, DRAM 512 MB or higher
Supported Operating System	Microsoft Windows XP SP2 or Above, Framework 2.0
Users	From 4 to 20 simultaneous Users (Unicast)
Alarm and Event Management	Events Triggered by Video Motion Detection Notified by Email/ Upload JPEG Images to FTP
Pick up Element	Sony CCD Image Sensor
Number of Pixels	<NTSC>510(H) x 492(V) <PAL>512(H) x 582(V)
AES	ON
AWB	ON-OFF
BLC	ON-OFF
Sync. Mode	Internal Sync
Scanning System	2:1 Interlace
Resolution	420TV Lines
S/N Ratio	More than 48 dB
Gamma	0.45
Minimum illumination	0.5 Lux , F1.4 (0 Lux with IR)
Infrared	Quantity
	Radiant Distance
LED	20 meters
Horizontal Sync. Frequency	<NTSC> 15.734KHz
Video Output	1.0Vp-p,75ohm
Power Source	DC12V
Power Consumption	3.8W
Operating Temperature	-20F~+120F
Lens	4/6/8 mm Board Lens
Shutter Control	<NTSC>1/60~1/100,000 sec
Dimension	68.5(ø)x 98(L) mm
Net Weight	0.3 Kg